


Dual Fiber 16CH C41-C56 DWDM MUX DEMUX and EXP Port, LC/UPC, LGX Box



The 16ch DWDM MUX DEMUX is designed by FIBERWDM, wavelength from C41 to C56(1544.53nm~1532.68nm),(By the way, we can support customize other waves); in accordance with the ITU-T G.694.1 100GHZ grid, it maximizes the capacity of the C-band range.

The 16ch DWDM is totally passive DWDM device, and support low insertion loss( wavelength ports<3.5dB;). And it conjunct with The DWDM amplifiers and DCM device, the 16ch DWDM transfer system can support a long distance transmission.


**Product Panel**



**16CH DWDM MUX DEMUX Dual Fiber**

Expansion Port for Future Bandwidth Increasing, makes it possible to increase the network capacity by connecting it to the line port of another DWDM MUX/DEMUX supporting different wavelengths, without the need of installing or leasing additional fibers.

**Line Link**



**16CH DWDM MUX DEMUX Dual fiber transmission**

16 Channels DWDM MUX DEMUX supports 16 channels difference business in two optical fiber for point-to-point transmission.


It works in Broadcast and TV, IDC, finance, government, cloud, massive data and other industries.

**Product Specification**

<b>Wavelength</b>	16channels C41-C56	<b>Channel Spacing</b>	100GHz (0.8nm)
<b>Channel Passband</b>	±0.11nm	<b>Technology</b>	TFF (Thin Film Filter)
<b>Insertion Loss</b>	≤ 3.5dB	<b>Link Loss</b>	≤ 4.5dB
<b>Center Wavelength Accuracy</b>	±0.05nm	<b>Return Loss</b>	≥ 45dB
<b>Directivity</b>	≥ 45dB	<b>Polarization Mode Dispersion</b>	≤ 0.1ps
<b>Polarization Dependent Loss</b>	≤ 0.3dB	<b>Channel Isolation</b>	Adjacent ≥30dB
<b>Channel Isolation</b>	Non-adjacent ≥ 45dB	<b>Temperature</b>	Operating -40 to 85°C Storage -40 to 85°C
<b>Net Weight</b>	LGX Box: 0.5KG 2slot 1U Rack: 3.5KG	<b>Dimensions (HxWxD)</b>	LGX Box: 220*200*39mm 1U Rack : 44*440*230mm

Note: Specified with connectors.

**Package Information**



**LGX BOX Plug in 2-Slot 1U Rack**



**2-Slot 1U Rack for LGX BOX**

**Order Information**

Product No.	Product description
DMD16-LGX01-C4156	DWDM MUX DEMUX 16CH (C41-C56) With EXP Dual fiber, LC/UPC , LGX Box
1U02-2LGX	19" inch 1U rack with 2 slot for Plug-in LGX box, 440*230*44mm

**Note: We Support Customized Design, please contact us by email.**